

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

(11) International Publication Number:

WO 98/12998

A61F 5/56, A63B 23/18, 71/00

A1

(43) International Publication Date:

2 April 1998 (02.04.98)

(21) International Application Number:

PCT/AU97/00634

(22) International Filing Date:

25 September 1997 (25.09.97)

(30) Priority Data:

65890/96

27 September 1996 (27.09.96)

(71) Applicant (for all designated States except US): STRATTON, Sarita, May [AU/AU]; Waters Road, Bridgewater, S.A. 5155 (AU).

(71)(72) Applicant and Inventor: STRATTON, Barric, Raymond [AU/AU]; Waters Road, Bridgewater, S.A. 5155 (AU).

(74) Agent: COLLISON & CO.; 117 King William Street, Adelaide, S.A. 5000 (AU).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, (US) UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


Published

With international search report.

(54) Title: BREATHING ASSISTANCE IMPROVEMENTS

(57) Abstract

Assistance for breathing is provided for both humans and animals by providing for a member (1) to adhere along only one or separately both sides of a nose and having a shape so that a part of the member (6) can adhere over a bone of the nose and then in cantilever fashion adhere to and thereby support soft flesh forming an outer side of a nasal passage so as to keep this open even with heavy breathing.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	F1	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Togo
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Tajikistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkmenistan
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Turkey
BJ	Benin	IE	Ireland	MN	Mongolia		Trinidad and Tobago
BR	Brazil	IL	Israel	MR	Mauritania	UA UG	Ukraine
BY	Belanus	IS	Iceland	MW	Malawi	US	Uganda
CA	Canada	IT	Italy	MX	Mexico	UZ	United States of Americ
CF	Central African Republic	JP	Japan	NE	Niger	VN	Uzbekistan
CG	Congo	KE	Кепуа	NL	Netherlands		Vict Nam
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	YU	Yugoslavia
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand	ZW	Zimbabwe .
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT			
CU	Cuba	KZ	Kazakstan	RO	Portugal		
CZ	Czech Republic	LC	Saint Lucia	RU	Romania		
DE	Germany	ũ	Liechtenstein	SD	Russian Federation Sudan		
DK	Denmark	LK	Sri Lanka	SE SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

BREATHING ASSISTANCE IMPROVEMENTS

This invention relates to a method and means to assist breathing for both humans and some animals.

The problem to which this invention is directed is the same problem as that set out in US Patent 5533499 which is directed to a nasal dilator which assists in resisting the drawing together of outer wall tissue of the nasal passage during breathing.

It is known that air passing through a nasal passage will, especially where that passage is other than circular, cause a drawing together of the closer walls through a bernoulli effect. This implicitly causes a further narrowing of the passageway. This effect is known to occur with many people. The result is that they may suffer sufficiently substantial restriction in passage cross sectional area that they can be forced to breathe additionally through their mouth or suffer effects such as snoring and even sleep apnoea. In other cases athletes can have their breathing restricted by this effect so limiting their performance.

US Patent 5533499 proposes a flexible strip which traverses from one side of the nose across the bridge of the nose to the other side and so that one end adheres to the skin adjacent one nasal passage and another end adheres to the skin adjacent the other nasal passage. The flexible strip has two resilient bands these being chosen so that they naturally spring apart and drag the skin and therefore the outer wall tissue outwardly to keep the respective passages more open.

An alternative system has a bifurcate arrangement which has respective legs in the respective nostrils and by, again, a natural springing apart, keeps the outer walls of the nose outwardly distended but from an inside of the nasal passageway.

I have found that the existing methods have disadvantages which can be reduced.

30 One of these is that the flexible strip traversing the bridge of the nose will be

implicitly visible and many are concerned by the appearance of this when being worn.

Further, the application of such a device will generally result in a continuous pulling pressure being applied so that the soft flesh of the nose will be under this continuous force. This can result over time in lack of comfort and possibly pain.

An object of this invention is to provide the public with a useful alternative.

According to one form of this invention there is provided an arrangement for assisting breathing wherein there is a member adhering to the external surface of one side only of a nose, the member extending along a side of the nose in a position so that the member is positioned to have a first part of the member adhering to the skin of the nose adjacent a bony structure located at a back of the nose, and the member has a further part which is closer to an inlet of the nostril of the nose than the first said part and adhering to the skin of the nose adjacent a soft part of the nose, with the member being shaped and otherwise being characterised so as to hold the soft part of the nose outwardly.

In preference the arrangement is further characterised in that there are two said members adhering to a nose with one member on a first one side of the nose of a wearer and the other member on a second opposite side of the nose of a wearer.

In preference as one alternative the nose is the nose of a person.

In preference as a further alternative the nose is the nose of a horse.

In preference as a further alternative again the nose is the nose of a dog.

In preference each member is in the form of a strip with a first sheet of material having an outermost face having thereon a pressure responsive adhesive adapted to maintain a selected shape of the soft tissue.

In preference there is an arrangement for assisting breathing wherein a member has a part at a first end attached by adhesion to skin immediately

adjacent bone toward a back of the nose of a user and a part at an opposite end of the member is attached by adhesion to the skin immediately above a portion of the nose toward a front of the nose which is soft flesh adjacent the nostril, and the member is shaped and positioned so as to effect a pulling outwardly of the flesh adjacent the nostril.

In preference the member is comprised of a laminate of a first pliable sheet with an outer surface coated by adhesive shaped and otherwise characterised to be located along a side of a nose, and a second pliable sheet holding the strut between itself and the first sheet.

- In a further preferred arrangement there is an arrangement for assisting breathing by being attachable by adhesion along one side of a nose to effect a maintaining of dilation to a nasal passage of the nose characterised in that the member is of elongate shape and is curved so as to have a face defining a convex shape and a contact adhesive being only on the convex side.
- In a further preferred arrangement there is an arrangement for assisting breathing by being attachable by adhesion along one side of a nose to effect a dilation force of a nasal passage characterised in that the member is a laminate comprised of a first pliable sheet with an outer surface coated by adhesive, a strut, and a second pliable sheet holding the strut between itself and the first sheet, the member being of elongate shape and is curved so as to have a side following a convex path and a contact adhesive being only on the convex side.

In preference for horses the angle is approximately 30 degrees.

In preference the strut is comprised of aluminium.

- For a better understanding of this invention it will now be described with reference to preferred embodiments which shall be described with the assistance of drawings wherein:
 - FIG 1 is a front view of a person with the arrangement according to the first embodiment fitted to both sides of their nose;
- 30 FIG 2 is a side view of the same embodiment installed in place on the side

of the nose;

- FIG 3 is an exploded view of the components making up the element of the first embodiment;
- FIG 4 is a side elevation of the element of the first embodiment;
- 5 FIG 5 is a side perspective view of a horse incorporating the invention according to a second embodiment;
 - FIG 6 is a plan view of the element according to the second embodiment; and
- FIG 7 is a side cross sectional view of the second embodiment as shown in preceding FIGS 5 and 6.

Now describing the embodiments and referring to the drawings in detail a member 1 in the form of a strip and comprised of a first sheet 2 having on an underneath side an adhesive chosen to enable contact pressure between the adhesive and the skin of a nose to ensure that adhesion will occur with sufficient strength upon an applied pressure between the two surfaces to then enable the member to act to pull or hold relevant skin of the nose and its underlying soft tissue in or into a dilation position.

The structure of a human nose is such that there is a hard part which is bone that starts about half way up or toward a back of the nose which bone is a part of the skull of the person. What is being achieved in accord with this invention is that this hard or bone part which is underlying flesh and skin to which the first end is adhered to which is shown to be further from the nostril of the nose than a dotted line at 3 and is used to support a part at a first end of the strip 1. This, as in the manner of a cantilever, can be used to "anchor" the one end of the strip 1 so that it can be used to locate and support in an appropriate position the part of the strip 1 at an opposite end of the strip (which is to say toward the part of a nose further down the face or toward an outer end of the nostril) so as to hold soft tissue of the side of the nose in an outwardly dilated position.

30 This is achieved by having the shape of the member defined by a strut 4 which

WO 98/12998 PCT/AU97/00634

is a thin strip of aluminium which is sandwiched between the sheet 2 and a top sheet 5 and has a shape that is elongated, and has a part at one Ind 6 approximately straight, and another part at an opposite end 7 approximately straight and these two parts 6 and 7 at respective opposite ends 9 and 10 are at an angle of approximately 60 degrees (shown at 8) one to the other.

The strut 4 is chosen from aluminium of 0.3 mm thickness and of a grade such that it is pliable and therefore can be changed in shape simply by using finger pressures but not so soft or pliable that when in position of holding a dilation position of the tissue of the nose that it will unduly distort and therefore not achieve sufficiently the result required. This can be readily tested for any user by simple trial and error. Aluminium sheet of this thickness of 0.3 mm as supplied from a manufacturer in Australia has been used satisfactorily both in a hardened state as supplied and also in a softened state by heating the hardened sheet for a period of several hours. Both materials performed adequately showing that a range of grades of materials and quality of materials will be useful.

Other materials can be used but aluminium sheet has been found to be most suitable. One of the characteristics that is useful is the fact that the aluminium apart from being pliable and therefore being able to be shaped by a user for comfort, is also resilient so that when deformed into a position by the user the aluminium can be resiliently deformed further. This can assist in applying further continuing tension adjacent a narrow part of the nasal passage. As a guide to the extent of resiliency that has been found to be useful the strut material in the embodiment having the dimensions of 15mm x 3mm x 0.3 mm if anchored at one end so as to be supported as a cantilever from 1mm of anchored end then 30 grams will deflect the outer end by 3mms. These dimensions are also the dimensions of the strut when bent as described that are most appropriate for use by adult humans for the invention. As a guide to the size range of a strut for adult humans the strut can be most usefully within the range of from 12-15 mm in length and 2.5-3.5 mm in width.

One of the advantages of the embodiment is that in use an effect of the strip is to act as a splint so that pressures or more correctly tensions applied will be contributed to by the natural springiness of the flesh to which the strip is attached. This means that, as the act of placing the strip in position means that one will distort the flesh to have this adhere to the relative positions of the

WO 98/12998 PCT/AU97/00634

6

5

25

30

parts of the strip, this will mean that the flesh will be held from returning to an original position by the splint ffect of the strip. This compares with a strip that bridges the nose which in a commercial production situation needs to be of a size to apply to all manner of sizes and shapes of noses. Accordingly this needs to be able to spring apart substantially and therefore the result is that this will have a tendency to apply constant tension over a substantial range of movement. It is this that over time can become quite uncomfortable.

By having an arrangement that will have a reference position that is immediately adjacent (this is the bone) the position of the applied tension means that this will implicitly provide a predominately position reference as compared to a maintained tension. The result provides more comfort for a user.

The bend in the strut 4 is located just adjacent to where a hard part (the bone) beneath or adjacent the soft tissue of the nose begins. If this is located fully on the hard part of the nose then it is found that soreness can develop after only some few hours of use because there will be a continuous pressure point at the bend.

The material to be used for the sheets 2 and 5 and adhesive both for the outer face of the sheet 2 and the joining between the strut 4 and the sheet 5 is such that it will need to be compatible for use against the skin of humans. Hypoallergenic material is an appropriate material.

In use the element is located so that the bend is just below the hard (that is the bone) part of the nose and on one side of the nose and the soft tissue is then manipulated out by hand usually by the user so as to be adhered to the adhesive outer surface of the sheet 2. The strut can thereafter be changed in shape by finger pressure. The concept however is that this can then hold outwardly the soft tissue adjacent the narrow part of the nasal passage and therefore both resist it being drawn in when greater air volume passes through but also for day to day use for those with deformed nasal passage shapes or those suffering from incidental blockage from rhinitis will also find value in the arrangement.

This concept therefore differs in some important ways from that disclosed in the US Patent in that this concept is found not to be so visually obvious

because it does not go across the bridge of the nose. Further it seems to allow for more comfortable use and from experiments conducted so far the results appear to be even more effective in providing nasal clearance. This is believed to be the case because the strip acts more in the manner of a splint and does not need to be designed to allow for continuous outward pressure or more correctly tension but rather simply to allow for holding of the flesh against contracting inwardly or at least against being pulled inwardly by reduced air pressure when air is breathed through the nasal passage.

The elements can be used for one side only of the nose if desired.

- Now I refer to FIGS 5, 6 and 7 which illustrate the application of the invention to a horse. This is an arrangement very similar to that described for the first embodiment in that the element 11 is comprised of three layers where a first is a sheet 12 with an outermost contact adhesive at 13, a middle layer is a strut 14 comprised of 0.3 mm thickness 6 mm width and 90 mm length of aluminium, and the top sheet 15 covers the other two layers. The strut 14 is bent in the middle at 16 to have two ends 17 and 18 that are each approximately straight but which are inclined 30 degrees one to the other as shown at 16.
- The shape of the nasal passage of a horse 20 and the location of a hard part (bone) 21 closely behind the open end of the nostril has meant that the concept works very well also for horses. Accordingly, as shown, the element 11 is attached to be in line along the elongate direction of a horses head 22 and is placed in position by opening the nostril passage out to then be held in the position shown with the strut acting in the manner of a splint to hold against retraction of the flesh.

The same arrangement is used for both sides of the horses head. In practise the arrangement gives very good results for these animals and it is believed that accordingly other animals that need to have enhanced performances such as dogs and sometimes camels may also be advantaged.

The results achieved from trials conducted so far have been outstanding. The strips when in place on a human as described have been able to be worn with great comfort over many days without concern. Further, their location has been appropriate to enable substantial disguise of the strips when in place.

P rhaps even more exciting has been that the medical results hav been substantial so that there have been on controlled tests substantial improvement in breathing efficiencies as compared to the strips when used that bridge the nose.

10

15

25

30

CLAIMS

- 1. An arrangement for assisting breathing wherein there is a member adhering to the external surface of one side only of a nose, the member extending along a side of the nose in a position so that the member is positioned to have a first part of the member adhering to the skin of the nose adjacent a bony structure located at a back of the nose, and the member has a further part which is closer to an inlet of the nostril of the nose than the first said part and adhering to the skin of the nose adjacent a soft part of the nose, with the member being shaped and otherwise being characterised so as to hold the soft part of the nose to support the flesh to support dilation of the nasal passage.
- 2. An arrangement as in claim 1 further characterised in that there are two said members adhering to a nose with one member on a first one side of the nose of a wearer and the other member on a second opposite side of the nose both being in a position as set out.
- 3. An arrangement for assisting breathing as in either one of claim 1 or 2 where the nose is the nose of a person.
- 4. An arrangement for assisting breathing as in either one of claim 1 or 2 where the nose is the nose of a horse.
- 2.0 5. An arrangement for assisting breathing as in either one of claim 1 or 2 where the nose is the nose of a dog.
 - 6. An arrangement for assisting breathing as in any one of the preceding claims further characterised in that each member comprises a first sheet of material having an outermost face having thereon a pressure responsive adhesive, a strip attached to a back side of the first said sheet and adapted to maintain a selected shape of the strip to effect a maintenance of the selected position of the soft tissue and therefore its dilation effect.
 - An arrangement for assisting breathing as in any one of the preceding claims further characterised in that each member is comprised of materials such that its shape is sufficiently pliable to enable manual change of shape.


30


- An arrangement for assisting breathing characterised by being a member having a part of the member attached by adhesion to skin immediately above a bony part of the nose and a further part of the member being attached by adhesion to skin adjacent a portion of the nose which is soft flesh adjacent the nostril, whereby the member is such as to and is positioned so as to effect a retention of an outward dilation on an outer wall of the nasal passage.
- An arrangement for assisting breathing as in the immediately preceding claim further characterised in that the member is comprised of a laminate of a first pliable sheet with an outer surface coated by a contact adhesive, a strut of deformable material, and a second pliable sheet holding the strut between itself and the first sheet.
- 10. An arrangement for assisting breathing by being attachable by adhesion along one side of a nose to effect a maintaining of dilation to a nasal passage of the nose characterised in that the member is of elongate shape and is curved so as to have a face defining a convex shape and a contact adhesive being only on the convex side.
- 11. An arrangement for assisting breathing by being attachable by adhesion along one side of a nose to effect a maintaining of dilation to a nasal passage of the nose as in the immediately preceding claim further characterised in that the member is a laminate comprised of a first pliable sheet with an outer surface coated by adhesive, a strut, and a second pliable sheet holding the strut between itself and the first sheet, the member being of elongate shape and being curved so as to have a side following a convex path and a contact adhesive being only on the convex side of the first pliable sheet which is an outer side.
 - 12. An arrangement for assisting breathing as in either of the two immediately preceding claims further characterised in that an extent of the curve of the member is such that an orientation in alignment from one end will change through approximately 60 degrees to its other end.
 - 13. An arrangement for assisting breathing as in the preceding claim 10, or 11 further characterised in that the angle as an extent of the curve of the member is such that orientation from one end of the member will change


WO 98/12998

through approximately 30 degrees to its other end.

- 14. An arrangement as in any one of the preceding claims 10,11, 12 or 13 where the size of the member being for a human adult lies within the range of from 12 to 15 mm in length and 2.5 to 3.5 mm in width.
- 5 15. An arrangement as in any one of the preceding claims 10,11, 12, 13 or 14 further characterised in that the strut is comprised of aluminium.
 - 16. An arrangement substantially as described in the specification with reference to and as illustrated by FIGS 1-4 of the accompanying drawings.
- 17. An arrangement substantially as described in the specification with reference to and as illustrated by FIGS 5, 6 and 7 of the accompanying drawings.







INTERNATIONAL SEARCH REPORT

International Application No.
PCT/AU 97/00634

_	LASSIFICATION OF SUBJECT MATTER			
Cl ⁶ : A	61F 5/56; A63B 23/18, A63B 71/00			
cording to Ir	sternational Patent Classification (IPC) or to both nati	ional classification and IPC		
	TELDS SEARCHED			
inimum docum	nentation searched (classification system followed by classi A61F; A63B; A62B; A61M	fication symbols)		
ocumentation	searched other than minimum documentation to the extent	that such documents are included in the	ne fields searched	
ectronic data /PAT, JAPI	oase consulted during the international search (name of dat O (NOSE: OR NOSTRIL: OR NARE: OR N IMPROV:)(S)(BREATH: OR INHAL: OR	WOWT) WIND I(WOOTO 1, OIL	terms used)	
	DOCUMENTS CONSIDERED TO BE RELEVANT			
Сацедогу*	Citation of document, with indication, where appropriate appropria	priate, of the relevant passages	Relevant to claim N .	
A	US,A, 5553605 (MUCHIN) 10 September 1996 whole document		1-15	
A	US,A, 5549103 (JOHNSON) 27 August 1996 whole document	1-15		
A	US,A, 5546929 (MUCHIN) 20 August 1996 whole document		1-15	
X	Further documents are listed in the continuation of Box C	X See patent family a	nnex	
Spece "A" documol of "E" earliintee "L" documor or vano "O" documor exh	later document published after the priority date and not in conflict wit understand the principle or theory document of particular relevance; to be considered novel or cannot be conventive step when the document document of particular relevance; be considered to involve an invent combined with one or more other combination being obvious to a ped document member of the same pa	h the application out cited to underlying the invention the claimed invention cannot onsidered to involve an is taken alone the claimed invention canno- ave step when the document such documents, such erson skilled in the art tent family		
	but later than the priority date claimed actual completion of the international search	Date of mailing of the international s 2 2 OCT 199	earch report	
Name and n AUSTRALI PO BOX 20 WODEN A AUSTRAL	CT 2606	Authorized officer MATTHEW FORWARD Telephone No.: (02) 6283 2606		

INTERNATIONAL SEARCH REPORT

International Application No.

	ation) DOCUMENTS CONSIDERED TO BE RELEVANT					
Category*	Citation of document, with indication, where appropriate, of the relevant pa		Relevant to claim No.			
Α	WO A 94/23675 (CREATIVE INTEGRATION & DESIGN, INC.) 27 Octo	ber 1994	Ciami No.			
			1			
			•			
!	•					
[
İ						
			,			
Ī						
			•			
1						

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No. PCT/AU 97/00634

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

atent Document Cited in Search Report		Patent Family Member					
US	5553605	AU	60981/96	EP	757905	EP	778014
		wo	9702793	US	5611334	US	5546929
US	5549103	AU	21806/92	BR	9206119	CA	2109953
		CN	1067574	EP	588949	` IL	101989
		wo	9222340	US	5476091	US	5533499
		US	5533503	US	5549103	US	5653224
		AU	66299/94	wo	9423675	AU	29557/95
		CA	2192001	EP	767642	NO	970026
		PL	318041	wo	9601093		
US	5546929	AU	60981/96	EP	757905	EP	778014
		JP	9024106	wo	9702793	US	5611334
		US	5553605				
wo	9423675	AU	66299/94	US	5549103	AU	21806/92
		BR	9606119	CA	2109953	CN	1067574
		EP	588949	IL	101989	NZ	242881
		wo	9222340	US	5476091	US	5533499
		US	5533503	US	5653224	AU	29557/95
		CA	2192001	EP	767642	NO	970026
		PL	318041	wo	9601093		

END OF ANNEX